761 SERIES GRIP-TITE (PUSH-LOK) HOSE

MSHA approved, lightweight, flexible, low pressure, general purpose hose with one fiber braid reinforcement. **Good for use with gasoline and diesel fuels**. Also used for conveying hydraulic oils, antifreeze solutions, most agricultural sprays and other diluted chemical solutions.



THE SPECIAL BRAIDING PROCESS USED IN THE MANUFACTURE OF THIS HOSE PERMITS THE USE OF GRIP (LOK) TYPE FITTINGS, WHICH ELIMINATES THE NEED FOR CLAMPS.

HOSE SPECIFICATIONS:

MSHA Approved

- **TUBE:** Black Nitrile for exceptional fuel and oil resistance.
- **COVER:** Chloroprine for abrasion, flame, oil and weather resistance.
- **REINFORCEMENT:** One textile braid.
- **COLORS:** Black, Grey (Blue and Red RTO)
- **PACKAGING:** 50, 100 FT Coils, Plastic Reels
- **FITTINGS:** 700 Series
- **WORKING TEMPERATURE:** -40°C to +100°C, -40°F to +212°F

PART No.	Hose I.D. (IN.)	Hose O.D. (IN.)	Working Pressure (P.S.I.)	Length (FT.)	Weight (LBS/FT.)
761-4-REEL	1/4	0.551	300	500	0.10
761-5-REEL	5/16	0.618	300	500	0.12
761-6-REEL	3/8	0.689	300	500	0.15
761-8-REEL	1/2	0.811	300	500	0.18
761-10-REEL	5/8	0.917	300	500	0.20
761-12-REEL	3/4	1.047	300	250	0.22

Copyright Fairview Ltd 2021