BREATHER VENTS (BBV Series)

Low profile breather vents used on single acting cylinders or valves with, Pipe thread or O-Ring Boss thread, to prevent dirt and foreign particles from entering ports open to the atmosphere. Also used for vacuum relief in pressure equalization of gear boxes, crank cases, storage tanks or reservoirs.

PART Number	BBV-A	BBV-B	BBV-C	BBV-D
Connection (NPTM)	1/8"	1/4"	3/8"	1/2"
Overall Length (IN.)	15/32"	21/32"	3/4"	31/32"
Hex (IN.)	15/32"	19/32"	23/32"	53/64"
Body Material	Brass			
Element Material	Sintered Bronze (40 micron standard)			
Max Operating Pressure	150 Psi (10.55 kg/cm^2)			
Operating Temperature	35°~300°F (1.6°~149°C)			
Weight (Approx.) OZ	0.18	0.34	0.55	1.05

BBV Series



PART Number	BBV-ORB-4	BBV-ORB-6	BBV-ORB-8	BBV-ORB-10	BBV-ORB-12
Connection (SAE)	7/16"-20	9/16"-18	3/4"-16	7/8"-14	1-1/16"-12
Overall Length (IN.)	47/64"	53/64"	15/16"	1-11/64"	1-11/32"
Hex (IN.)	9/16"	11/16"	7/8"	1-11/64"	1-11/32"
Body Material	Brass				
Element Material	Sintered Bronze (70 micrzon)				
Max Operating Pressure	150 psi (10.55 kg/cm²)				
Operating Temperature	35°~300°F (1.6~149°C)				
Weight (OZ.)	0.42	0.71	1.18	2.30	3.90



BBV-ORB Series

Copyright Fairview Ltd. 2020