

PREMIUM NITRILE RUBBER HOSE (RNH SERIES)

Fairview's Nitrile Hose with MSHA cover offers a combination of flexibility, resistance to ignition, chemicals, heat, oil, UV, ozone and weathering, all contributing to its durability and excellent abrasion resistance.

Non-conductive 1 megohm per inch of hose length at 1000 Volts DC

ACCUTEK
RNH-4 1/4" ID/DI (6.4mm) MSHA NON-CONDUCTIVE/NON-CONDUCTEUR 300 PSI WP/PS -40°C (-40°F) MMY

HOSE SPECIFICATIONS:

- **TUBE:** Nitrile Rubber (ARPM Class A)
- **COVER:** Pin-pricked Special Synthetic Nitrile (ARPM Class B)
- **REINFORCEMENT:** Two Layers of High Strength Fiber
- **COLOR:** Red
- **WORKING TEMPERATURE:** -40°C to +121°C, -40°F to +250°F
- **FITTINGS:** Hose barbs / Hose inserts

Part No.	Hose I.D.	Hose O.D. (IN)	W.P. (PSI)	Wgt./Ft. (LBS)	Length (FT)	Bend Rad.(IN)
RNH-4-REEL	1/4	0.50	300	1.23	300	2.6
RNH-6-REEL	3/8	0.69	300	1.81	300	3.0
RNH-8-REEL	1/2	0.84	300	2.75	300	4.9
RNH-10-REEL	5/8	1.00	300	3.54	300	5.9
RNH-12-REEL	3/4	1.14	300	4.34	300	7.1
RNH-16-REEL	1	1.47	300	5.79	300	9.8