PIPE THREAD SEALANT
PRO-DOPE SERIES

PRODUCT OVERVIEW

MASTERS® PRO-DOPE® is a non-toxic, non-corrosive, non-hardening thread sealant designed for sealing metal and plastic threaded connections. The formula will not dry out, stain, harden, or separate, while lubricating threads during assembly and allowing easy disassembly even after years of service. PRO-DOPE® effectively seals most liquids and gases against leakage up to 10,000 PSI.



Part Number	Description
TTS-250	250 mL (1/2 Pint) Brush-Top Can
TTS-500	500 mL (1 Pint) Brush-Top Can

Property	Specification
Max Pressure	10,000 PSI
Temperature Range	-129°C to 204°C (-200°F to 400°F)

FEATURES

- Non-hardening formula
- For metal & plastic threads
- Non-toxic and non-corrosive
- Will not dry out or separate
- Lubricates threads during assembly
- Easy disassembly after service

APPLICATION

- Compressed air systems
- Natural gas & propane systems
- Water systems
- Steam systems
- Hydraulic systems
- Fuel and oil systems
- Refrigeration systems

NOTE: Suitable for most liquids and gases including air, natural gas, propane, water, steam, petroleum products, and hydraulic oils. Verify compatibility with the intended media prior to use.

CFIA "Letter of No Objection" Available

Certifications & Compliance

- ULC Listed for Natural Gas ((CAN/ULC - S642) and NSF/ANSI 61G/372 listed for potable water.
- MAS Green Certified
- Low VOC Formulation
- WHMIS Labelled

Copyright Fairview Ltd. 2020