

INDUSTRIAL PIPE THREAD SEALANT

PRO-BLUE SERIES

PRODUCT OVERVIEW

MASTERS® PRO-BLUE® is a non-toxic, non-corrosive, non-hardening thread sealant formulated for metal and plastic threaded connections. Designed to resist drying, hardening, and separation, it provides reliable sealing performance while allowing easy disassembly after extended service.

Part Number	Description
TTSB-250	250 mL (1/2 Pint) Brush-Top Can
TTSB-500	500 mL (1 Pint) Brush-Top Can

Property	Specification
Max Pressure	10,000 PSI
Temperature Range	-129°C to 204°C (-200°F to 400°F)

FEATURES

- Non-hardening formula
- For metal and plastic threads
- Non-toxic and non-corrosive
- Resists drying and separation
- Lubricates threads during assembly
- Easy disassembly after service

APPLICATION

- Compressed air systems
- Natural gas systems
- Propane and LPG systems
- Water systems
- Steam systems
- Hydraulic systems
- Fuel and oil systems
- Refrigeration systems

NOTE:

- Suitable for most liquids and gases.
- Not recommended for oxygen service.
- Exercise caution with chemicals having low surface tension.
- Verify compatibility with the intended media prior to use.



Certified to
NSF/ANSI CAN 61-G & 372



Certifications & Compliance

- ULC Listed for Natural Gas ((CAN/ULC - S642) and NSF/ANSI 61G/372 listed for potable water.
- MAS Green certified.
- Low VOC
- WHIMIS labelled